



Section Width (W)	inches		18
Section Depth (D)	inches		10
Flange Thickness (T)	inches		0.410
Weight (per linear foot)	pounds		8.0
Moment of Inertia	In <sup>4</sup> /ft		132.8
Section Modulus	In <sup>3</sup> /ft		26.5
Modulus of Elasticity	psi	ASTM D638	380,000
Allowable Moment	ft-lbs/ft		8,110
Tensile Strength	psi	ASTM D638	6,000
Izod Notched Impact	lb/in	ASTM D256	13.75
Heat Deflection Temperature	degrees F	ASTM D648	158

**Available Colors** Tidewall Vinyl Sheet Piling comes in a standard color of light gray, but it is also available in white, tan, brown, and other custom colors upon request.

**UV Protection** All Tidewall Products are produced from highly weatherable, UV-stabilized rigid PVC.

**Lifetime Warranty** Tidewall Vinyl Sheet Piling products are covered by a transferable Lifetime Limited Warranty that protects against manufacturing defects.

The information provided are nominal values and are believed to be accurate. To insure that you select the proper Tidewall Vinyl Sheet Piling product for your particular application, Tidewall recommends that you consult with a qualified local engineer and/or contractor. Tidewall makes no warranty of any kind as to the suitability of Tidewall Vinyl Sheet Pile for a particular application, or the results obtained therefrom.